5.0mm Round Type LED Lamps

'

MODEL NO: IE-5WC4ST-18

★Features:

- Fluorescence Type;
- High Luminous Intensity;
- High Efficienty;

★Lens Color:

□ Color Diffused □ Color Transparent

☑ Water Clear ☐ White Diffused

★Descriptions:


• The white LED which was fabricated using a blue LED and a phosphor, and the phosphor is excited by blue light and emits yellow fluorescence. The mixture of blue light and yellow light results in a white emission.

★Applications:

- OA Equipment;
- Backlighting of LCD;
- Automotive Equipment;
- Replacement of Conventional Light Bulbs and Fluorescent Lamps.

★Absolute Maximum Ratings (Ta=25°C):

★Package Dimension:



*Attention

- 1, All dimensions are in millimeters (inches).
- 2. Tolerance is ± 0.25 mm(0.01") unless otherwise specified.
- 3. The outstanding gum edge part is biggest not very in 1.5mms.
- 4. The long feet is a LED Anode.

Parameter	Symbol	Rating	Unit	Remarks		
Forward Current	I_{F}	30	m A			
Peak Forward Current	$I_{ t FP}$	100	m A	1/10 Duty Cycle		
Reverse Voltage	V_{R}	5	V			
Operating Temperature	Topr	-25 ~+85	°C			
Storage Temperature	Tstg	-40 ~+100	°C			
Soldering Temperature	Tsol	260	°C	<3 seconds		
Power Dissipation	Pd	100	mW			

★Electronic Optical Characteristics(Ta=25°C):

Part Number	Emitting Color	V _F (V) I _F =20mA		IV(med) I _F =20mA		I _R (μ A)	Chromaticity Coordinates		Viewing Angle	
		Min	Тур	Max	Тур	Max	VR=5V	X	Y	201/1(*)
IE-5WC4ST-18	WHITE	2.8	3.1	3.8	15000	20000	< 10	0.24-0.28	0. 23-0. 29	20°

★Elucidation: Pb = Pb free Soldering Application, Pb < 1000ppm (RoHS-Compliant)