

0.52" Dual Digit LED Display

Model NO. : IE-2G-105213-GC-P15.24

Chip (Ta=±25℃)		PIN	Drive Mode	Face
Quantity	Emitting color	10.28mm	Common Anode	
16ea	Yellow Green			Gray

■ Package Outlines (unit:mm)

Notes:

1. All dimensions are in millimeters (inches);
2. Tolerances is $\pm 0.25 (0.01")$ unless otherwise noted.

■ Internal Circuit:

0.52" Dual Digit LED Display

Model NO. : IE-2G-105213-GC-P15.24

■ Absolute Maximum Ratings (Ta=+25℃)

Characteristics	Symbol	Rating	Unit	Remarks
Forward current/segment	I_F	30	mA	——
Peak forward current/segment	$I_{F(Peak)}$	100	mA	1/10 Duty Cycle
Reverse Voltage/segment	V_R	5	V	——
Operating Temperature	T_{opr}	-25~+80	℃	——
Storage Temperature	T_{Stg}	-40~+85	℃	——
Solder Temperature	T_{Sol}	260	℃	≤5 seconds
Power Dissipation/segment	P_d	65	mw	——

■ Electro-Optical Characteristics (Ta=25℃) :

Parameter	Symbol	Test condition	Min.	Typ.	Max.	Unit
Forward Voltage/segment	V_F	$I_F=20mA$	1.8	2.1	2.6	V
Dominant Wavelength	λ_D	$I_F=20mA$	565	570	575	nm
Spectrum width (Half value)	$\Delta \lambda$	$I_F=20mA$	——	35	——	nm
Luminous Intensity/segment	I_V	$I_F=20mA$	——	35	——	mcd
Reverse current/segment	I_R	$V_R=5V$	——	——	10	μA