5.0mm Round Type LED Lamps

MODEL NO: IE-51W4UT-27D

★Features:

- Fluorescence Type;
- High Luminous Intensity;
- High Efficienty;

★Lens Color:

□ Color Diffused □ Color Transparent

☑ Water Clear ☐ White Diffused

★Descriptions:


• The white LED which was fabricated using a blue LED and a phosphor, and the phosphor is excited by blue light and emits yellow fluorescence. The mixture of blue light and yellow light results in a white emission.

★Applications:

- OA Equipment;
- Backlighting of LCD;
- Automotive Equipment;
- Replacement of Conventional Light Bulbs and Fluorescent Lamps.

and Fluorescent Lamps. ★Absolute Maximum Ratings (Ta=25°C):

★Package Dimension:



*Attention

- 1, All dimensions are in millimeters (inches).
- 2. Tolerance is ± 0.25 mm(0.01") unless otherwise specified.
- 3. The outstanding gum edge part is biggest not very in 1.5mms.
- 4. The long feet is a LED Anode.

Parameter	Symbol	Rating	Unit	Remarks							
Forward Current	I_{F}	30	m A								
Peak Forward Current	$I_{ t FP}$	100	m A	1/10 Duty Cycle							
Reverse Voltage	V_{R}	5	V								
Operating Temperature	Topr	-25 ~+85	°C								
Storage Temperature	Tstg	-40 ~+100	$^{\circ}$ C								
Soldering Temperature	Tsol	260	°C	<3 seconds							
Power Dissipation	Pd	100	mW								

\bigstar Electronic Optical Characteristics (Ta=25°C):

Part Number	Emitting Color	V _F (V) I _F =20mA		IV(med) I _F =20mA		$I_R(\mu A)$	Chromaticity Coordinates		Viewing Angle	
		Min	Тур	Max	Тур	Max	VR=5V	X	Y	2θι/t (*)
IE-5IW4UT-27D	Warm White	2.6	3.0	3.6	6000	12000	< 10	0.37-0.42	0.37-0.42	60°

★Elucidation: Pb = Pb free Soldering Application, Pb < 1000ppm (RoHS-Compliant)

▲ LEDs ▲ LED Displays ▲ Infrared LEDs ▲ LCD Backlight

▲ LED Light