



PANEL THICKNESS	X
1.0~2.0	21
2.0~3.0	21.5

No.	Name	Material	Qty
1	Base	PA66	1
2	Grounding pin	Brass t2.0	1
3	current-carrying pin	Brass t2.0	2

Standard:

- IEC 60320-1
- GB/T 17465.1

Rating :

- 15A 250V AC T105 UL cUL
10A 250V AC TUV 3C KC CE

Terminal Strength: $\geq 80N$

Withstand Voltage: Between all terminals: 2500VAC (50-60Hz) 1min
terminals to Base: 3750V AC (50-60Hz) 1min

Leakage Current : 1mA

Insulation Resistance: $\geq 100M\Omega$ 500V DC

Glow-wire temp: 750°C



YUEQING LANZ Electronics Co., Ltd

COMMON TOLERANCE :

UP TO 5	± 0.20
ABOVE 5 TO 30	± 0.30
ABOVE 30	± 0.50
ANGULAR	$\pm 5^\circ$

PROJECTED	PRODUCT NAME	Ac Inlet C14	SCALE	Free

UNIT	mm	UNITS	DATE	APPROVAL BY	DWG NO.	LANZ/CRS-LZ142F
UP TO 5	± 0.20	UNIT	2024.6.14			
ABOVE 5 TO 30	± 0.30	DRAWN BY				
ABOVE 30	± 0.50	WU YU				

ISSUE	REVISION	DESCRIPTION	DATE

REV.	DATE	REVISION	DESCRIPTION
A4			
A3			
A2			
A1			