## 10mm Round Type LED Lamps

MODEL NO: IE-10WW-UB-C-C

#### ★Features:

- Fluorescence Type;
- High Luminous Intensity;
- High Efficienty;

### ★Lens Color:

□ Color Diffused □ Color Transparent

☑ Water Clear ☐ White Diffused


# ★Descriptions:

• The white LED which was fabricated using a blue LED and a phosphor, and the phosphor is excited by blue light and emits yellow fluorescence. The mixture of blue light and yellow light results in a white emission.

## ★Applications:

- OA Equipment;
- Backlighting of LCD;
- Automotive Equipment;
- Replacement of Conventional Light Bulbs and Fluorescent Lamps.

### ★Package Dimension:



### \*Attention

- 1, All dimensions are in millimeters (inches).
- 2. Tolerance is  $\pm 0.25$ mm(0.01") unless otherwise specified.
- 3. The outstanding gum edge part is biggest not very in 1.5mms.
- 4. The long feet is a LED Anode.

## ★Absolute Maximum Ratings(Ta=25°C):

Parameter	Symbol	Rating	Unit	Remarks	
Forward Current	$I_{\mathrm{F}}$	30	m A		
Peak Forward Current	$I_{FP}$	100	m A	1/10 Duty Cycle	
Reverse Voltage	$V_R$	5	V		
Operating Temperature	Topr	-25~+85	$^{\circ}\!\mathbb{C}$		
Storage Temperature	Tstg	-40 ~+100	$^{\circ}$		
Soldering Temperature	Tsol	260	$^{\circ}$	≪3 seconds	
Power Dissipation	Pd	80	mW		

## ★Electronic Optical Characteristics (Ta=25°C):

Part Number	Emitting Color	$V_{F}(V)$ $I_{F}=20$ mA		I V(mcd) I <sub>F</sub> =20mA		I <sub>R</sub> (μ A)	Chromaticity Coordinates		Viewing Angle	
		Min	Тур	Max	Тур	Max	VR=5V	X	Y	2θ <sub>1/2</sub> (°)
IE-10WW-UB-C-C	Warm White	2.8	3.0	3.6	13000	29000	<b>&lt;</b> 10	0.46-0.50	0.44-0.47	30°

★Elucidation: Pb = Pb free Soldering Application, Pb < 1000ppm (RoHS-Compliant)