

IE-2TC

Automatic Side/Horizontal Feed Wire Stripping and Crimping Machine

Features

- Effective solution for ultra-fine wires
- Specialy compatible with multi-core cable

Technical Data

| | |
|---------------------------------|--|
| Raw material | PVC, Teflon, Silicone, Low halogen, Fiberglass, etc |
| Crimp force | 1.5 tons [Customizable] |
| Conductor cross-sections | 0.03 - 0.75 mm ² [AWG 32 - 18] [Customizable] |
| Stripping length | 1 - 10 mm |
| Stroke | 30 mm |
| Rated power | 450 W |
| Power supply | AC 110V - 220 V ± 10%, 50 / 60 Hz |
| Air supply | 0.3 - 0.6 MPa (clean and dry air) |
| Dimensions | L 600 x W 400 x H 850 mm |
| Weight | 68 KG |



IE-2TC END

Automatic Rear Feed Strip and Crimp Machine

Features

- Vertical / End feed terminal
- Shark teeth / 187 / 250 / O ring / Flat terminal
- 3 tons crimping force

Technical Data

| | |
|---------------------------------|---|
| Crimp force | 3 tons |
| Conductor cross-sections | 0.03 - 2 mm ² [Customizable] |
| Stripping length | 1 - 8 mm |
| Cutting accuracy | 0.05 - 1 mm |
| Position accuracy | 0.05 - 1 mm |
| Stroke | 50 mm |
| Power supply | AC 110V - 220 V ± 10%, 50 / 60 Hz |
| Air supply | 0.5 - 0.6 MPa (clean and dry air) |
| Dimensions | L 460 x W 520 x H 1100 mm |
| Weight | 105 KG |

