

---

<b>SAMPLE APPROVAL SHEET</b>
------------------------------

**Customer Name**

\_\_\_\_\_

**Part Number**

**IE-765Y-ST-L-BF-Y**

\_\_\_\_\_

**Sample Quantity**

\_\_\_\_\_

**Sample Date**

\_\_\_\_\_

<b>APPROVED    SIGNATURES</b>		

--	--	--

\_\_\_\_\_

\_\_\_\_\_

Part No:

# IE-765Y-ST-L-BF-Y

## Features:

- \* High intensity Polygonal LED lamp
- \*  $\Phi 5\text{MM}$  round shape
- \* UV resistant epoxy





## Applications:

- \* LED Lighting
- \* Automotive Lighting application

## Absolute Maximum Ratings (Ta=25°C)

Parameter	Symbol	Max	Unit
Power Dissipation	Ps	100	mW
Peak Forward Current	$I_{FF}$	60	mA
Continuous Forward Current	$I_F$	20	mA
Reverse Voltage	Vs	5	V
Operating Temperature Range	Topr	-30°C to +80°C	
Storage Temperature Range	Tstg	-40°C to +100°C	
Lead Soldering Temperatur $\Delta$	Tsol	260	°C

## Package Dimensions



Unit : mm

Tolerance are  $\pm 0.2$ , unless note otherwise

\* Duty ratio max 1/10 Pulse Width max. 0.1ms;

$\Delta$  At the position of 4mm from the bottom of the package within 5 seconds.

## Electrical Optical Characteristics

( $T_a=25^{\circ}\text{C}$ , @ $I_F=20\text{mA}$ )

Part No.	Material	Emitting color	Forward voltage(V)		Luminous Intensity(mcd)		Dominant Wavelength(nm)		Viewing Angle ( $2\theta_{1/2}$ )
			Min	Max	Min	Max	Min	Max	
<b>IE-765Y-ST-L-BF-Y</b>	AlGaInP	<b>Yellow</b>	1.8	2.2	2000	3000	588	592	$90\pm 10$

BIN Table : (Test at 20 mA)

VF (v)	
Code	Range
1	1.8-2.0
2	2.0-2.2






IV (mcd)	
Code	Range
1	2000-3000

Wd (nm)	
Code	Range
Y1	588-590
Y2	590-592

□ Luminous Intensity Measure tolerance are

### Caution in ESD.

1. Static Electricity and surge damages the LEDs. It is recommended to use a wrist band or anti-electrostatic glove when handling the LEDs. All devices、Equipment and machinery must be properly grounded.
2. When inspecting own final products on which LEDs were mounted, It is easy to find static-damaged LEDs by light emission test at lower current (below 1mA is recommended) .
3. Damaged LEDs will show some unusual characteristics such as leak current remarkably increases, starting forward voltage becomes lower, or the LEDs get unlighted at the low current.



## Reliability Test

Classification	Test Item	Test Conditions	Sample Size	Num of Damaged	Reference Standard
Endurance Test	Operating Life	$I_F=30\text{mA}$ 1000Hrs	22	0	MIL-STD-750:1026 MIL-STD-202:107D JIS C 7021:B-4
	High Temp. High Humidity Storage	$85\pm 5^\circ\text{C}$ 85-90% RH 1000Hrs	100	0	MIL-STD-202:103D JIS C 7021:B-11
	Hi-Temp. Storage	$100\pm 5^\circ\text{C}$ 1000Hrs	100	0	MIL-STD-750:2031 MIL-STD-202:210A JIS C 7021:B-10
	Low-Temp. Storage	$-55\pm 5^\circ\text{C}$ 1000Hrs	100	0	JIS C 7021:B-12
Environmental Test	Temperature Cycling	$-40\pm 5^\circ\text{C}$ 30min Room Temp. 5min $100\pm 5^\circ\text{C}$ 30min 100 Cycles	100	0	MIL-STD-750:1051 MIL-STD-202:107D JIS C 7021:A-4
	Thermal Shock	$-30\pm 5^\circ\text{C}$ 5min $100\pm 5^\circ\text{C}$ 5min 100 Cycles	100	0	MIL-STD-750:1051 MIL-STD-202:107D JIS C 7021:A3
	Solderability	$230\pm 5^\circ\text{C}$ Dwell Time $\leq 5\text{sec}$	22	0	MIL-STD-202:208D MIL-STD-750:2026 MIL-STD-883:2003 JIS C 7021:A-2
	Solder Resistance	$260\pm 5^\circ\text{C}$ $10\pm 1\text{sec}$	22	0	MIL-STD-750:2031 MIL-STD-202:210A JIS C 7021:A-1

## Criteria for Ju:

Item	Symbol	Test Conditions	Criteria for Judgment	
			Min	Max
Forward Voltage	$I_F$	$I_F=20\text{mA}$	-	U. S. L*1.1
Reverse Current	$I_R$	$V_R=5\text{V}$	-	U. S. L*2.0
Luminous Intensity	$I_v$	$I_F=20\text{mA}$	L. S. L*0.7	-

PS: U. S. L. :Upper Standard Level L. S. L. :Lower Standard Level