

# IE-F3

## 0.35 - 6mm<sup>2</sup> Ferrule Stripping Crimping Machine



### Features

- Loose piece tubular bootlace ferrules max length 12mm
- Insulated end sleeves ranging from 0.35 to 6.0 mm<sup>2</sup>
- Robust construction, reliable operation, industrial quality
- Deutsch solid contact can be crimped

### Technical Data

<b>Conductor cross-section</b>	0.35, 0.5, 0.75, 1.0, 1.5, 2.5, 4.0, 6.0 mm <sup>2</sup> [ changing vibrate bowl ]		
<b>Stripping length</b>	Inner wire: Max 15 mm    Outer sheath of multicore cable: Min 40 mm		
<b>Crimping shape</b>	Quadrilateral / Hexagonal / [ Customizable ]	<b>Crimping length</b>	6 - 12 mm
<b>Cycle time</b>	2.5 seconds, 1000 - 1300 pcs / hr	<b>Customize logo</b>	Yes
<b>Display</b>	4.3" color touchscreen, English / Chinese [ other languages on request ]		
<b>Data library</b>	100 programs	<b>Rated power</b>	400 W
<b>Air supply</b>	0.6 - 0.8 MPa ( clean and dry air )	<b>Power supply</b>	AC 110V - 220V ± 10%, 50 / 60 Hz
<b>Dimensions</b>	L 430 x W 505 x H 425 mm	<b>Weight</b>	68 KG