# 5.0mm Round Type LED Lamps

# MODEL NO: IE-5IW4ST-8C

#### ★Features:

- Fluorescence Type;
- High Luminous Intensity;
- High Efficienty;

#### ★Lens Color:

□ Color Diffused □ Color Transparent

☑ Water Clear ☐ White Diffused

# ★Descriptions:


• The white LED which was fabricated using a blue LED and a phosphor, and the phosphor is excited by blue light and emits yellow fluorescence. The mixture of blue light and yellow light results in a white emission.

# ★Applications:

- OA Equipment;
- Backlighting of LCD;
- Automotive Equipment;
- Replacement of Conventional Light Bulbs and Fluorescent Lamps.

#### ★Absolute Maximum Ratings (Ta=25°C):

### ★Package Dimension:



#### \*Attention

- 1, All dimensions are in millimeters (inches).
- 2. Tolerance is  $\pm 0.25$ mm(0.01") unless otherwise specified.
- 3. The outstanding gum edge part is biggest not very in 1.5mms.
- 4. The long feet is a LED Anode.

Parameter	Symbol	Rating	Unit	Remarks	
Forward Current	$I_{F}$	30	m A		
Peak Forward Current	$I_{ t FP}$	100	m A	1/10 Duty Cycle	
Reverse Voltage	$V_{R}$	5	V		
Operating Temperature	Topr	-25 ~+85	°C		
Storage Temperature	Tstg	-40 ~+100	°C		
Soldering Temperature	Tsol	260	°C	<3 seconds	
Power Dissipation	Pd	100	mW		

# $\bigstar$ Electronic Optical Characteristics (Ta=25°C):

Part Number	Emitting Color	V <sub>F</sub> (V) I <sub>F</sub> =20mA		IV(mcd) I <sub>F</sub> =20mA		$I_{R}(\mu A)$	Chromaticity Coordinates		Viewing Angle	
		Min	Тур	Max	Тур	Max	VR=5V	X	Y	201/1(*)
IE-5IW4ST-8C	Warm White	2.8	3.2	3.8	5000	10000	<b>&lt;</b> 10	0.37-0.42	0.37-0.42	30°

★Elucidation: Pb = Pb free Soldering Application, Pb < 1000ppm (RoHS-Compliant)