5.0mm Round Type LED Lamps

MODEL NO: IE-5W4SW-54

★Features:

- Fluorescence Type;
- High Luminous Intensity;
- High Efficienty;

★Lens Color:

□ Color Diffused

□ Color Transparent

□ Water Clear

✓ White Diffused

★Descriptions:


• The white LED which was fabricated using a blue LED and a phosphor, and the phosphor is excited by blue light and emits yellow fluorescence. The mixture of blue light and yellow light results in a white emission.

★Applications:

- OA Equipment;
- Backlighting of LCD;
- Automotive Equipment;
- Replacement of Conventional Light Bulbs and Fluorescent Lamps.

★Absolute Maximum Ratings (Ta=25°C):

★Package Dimension:



*Attention

- 1. All dimensions are in millimeters (inches).
- 2. Tolerance is ± 0.25 mm(0.01") unless otherwise specified.
- 3. The outstanding gum edge part is biggest not very in 1.5mms.
- 4. The long feet is a LED Anode.

Parameter	Symbo1	Rating	Unit	Remarks	
Forward Current	I_{F}	30	m A		
Peak Forward Current	IFP	100	m A	1/10 Duty Cycle	
Reverse Voltage	V_{R}	5	V		
Operating Temperature	Topr	-25 ~+85	°C		
Storage Temperature	Tstg	-40 ~+100	°C		
Soldering Temperature	Tsol	260	°C	<3 seconds	
Power Dissipation	Pd	100	mW		

★Electronic Optical Characteristics(Ta=25°C):

Part Number	Emitting Color	$V_F(V)$ $I_F = 20 \text{mA}$		$ \begin{array}{c} I V_{(\text{mcd})} \\ I_{_F} = 2 0 \text{mA} \end{array} $		I _R (μΑ)	Chromaticity Coordinates		Viewing Angle	
		Min	Тур	Max	Тур	Max	VR=5V	X	Y	201/1(*)
IE-5W4SW-54	WHITE	2.8	3.1	3.8	2300	5500	<10	0.26-0.31	0.28-0.33	50°

★Elucidation: Pb = Pb free Soldering Application, Pb<1000ppm(RoHS-Compliant)