

# **LED Display**

## Product Data Sheet

### IE-1B-15001B

Spec No.:

Effective Date: Sep 20, 2014

## FEATURES

5 inch (126mm) Digit Height  
Low Power Requirement  
High Brightness and High Contrast  
Excellent Characters Appearance  
IC Compatible , Easy Assembly  
RoHS Compliant

## DESCRIPTION

This is a 5 inch (126mm) digit height single digit seven segment LED display. This device utilizes blue LED chips, which are made from InGaN, and has a black face and white segments.

## DEVICE

Blue	Description
IE-1B-15001B	Common Anode, Right Hand Decimal
Total 101 Blue LED Chips	



**PIN CONNECTION**

<b>PIN NO.</b>	<b>CONNECTION</b>
1	COMMON ANODE
2	CATHODE E
3	CATHODE D
4	CATHODE C
5	CATHODE DP
6	CATHODE B
7	CATHODE A
8	COMMON ANODE
9	CATHODE F
10	CATHODE G

**ABSOLUTE MAXIMUM RATINGS AT Ta=25°C**

PARAMETER	SYMBOL	InGaN BLUE	UNIT
Power Dissipation Per Segment	PAD	70	mw
Reverse Voltage Per Segment	VR	5	V
Continuous Forward Current Per Segment	IAF	20	mA
Peak Forward Current Per Segment(Duty-0.1,1KHz)	IPF	100	mA
Operating Temperature Range	TOPr	-20°C to 80°C	
Storage Temperature Range	Tstg	-30°C to 85°C	
Lead Soldering Temperature 260°C at 1.6mm From Body for 3 second			

**ELECTRICAL/OPTICAL CHARACTERISTICS AT Ta=25°C****InGaN BLUE**

PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Forward Voltage, Per Segment	VF	IF=20mA	3	3.2	3.5	V
Reverse Current, Per Segment	IR	VR=5V			50	μA
Peak Emission Wavelength	λp	IF=20mA	460	462.5	465	nm
Luminous Intensity Per Segment	IV	IF=10mA	35	40	50	mcd
		IF=20mA	70	80	100	

TYPICAL ELECTRICAL / OPTICAL CHARACTERISTIC CURVES @ TA = 25°C

