




SPECIFICATIONS:

(top view) (bottom view)

Industry Standard Dimensions**IEC 60086-2:2000 Standards**DISCHARGE CHARACTERISTICS AT 1500Ω 25°C 60%RH
(Discharged 24 hours/day)**Chemical System:** Zinc Air (Zn/O₂)**Identification:** IEC-PR41**Tab Color:** Brown**Build Standard:** IEC 60086-2:2000,
IEC 60086-2:2011**Nominal Voltage:** 1.4 Volts**Capacity (IEC 60086-2:2000):** 170 mAh (to 0.90 volts)
(Rated at 1500 ohms at 20°C/ 60%RH)**Capacity (IEC 60086-2:2011):** 160 mAh (to 1.05 volts)
(Rated at 1.2 mA continuous & 5 mA / 100 ms Pulses at 25°C/ 60%RH)**Available Current:** 10 mA(at 1.1 volts)**Tab Sealing Arrangements:** On Cathode Can. See picture above.**Capacity Retention:** > 85%(after 3 years)**Shelf Life:** 3 years**Operation Temp:** 0°C to 50°C**Typical Weight:** 0.54 grams (0.02 oz.)**Typical Volume:** 0.17 cubic centimeters
(0.010 cubic inch)**Impedance:** ≤ 6 ohms (at AC 1000Hz)**Construction****ZeniPower Battery Co., Ltd.**Building 10, Xiang Zhou North Industry Park,
Zhuhai, GD 519002, ChinaE-mail: info@zenipower.comHome Page: www.zenipower.com


Tel: +86-756-252 6620 Fax: +86-756-252 6630

This data sheet is subject to change without prior notice.
Contact us for the latest information. Contents here do not
constitute a warranty.


May 2011

Discharge Charts of IEC 60086-2:2011 Standards

Hearing aid standard



Hearing aid high drain

**ZeniPower Battery Co., Ltd.**

Building 10, Xiang Zhou North Industry Park,
Zhuhai, GD 519002, China

E-mail: info@zenipower.com

Home Page: www.zenipower.com

Tel: +86-756-252 6620 Fax: +86-756-252 6630

This data sheet is subject to change without prior notice.
Contact us for the latest information. Contents here do not
constitute a warranty.

May 2011