



PRODUCT DATA SHEET


BASIC DIMENSIONS




PANEL CUTOUT



90° Bend TERMINAL DETAILS—



90° TERMINAL DETAILS—



SPECIFICATION TABLE

SR.NO.	PARAMETER		SPECIFICATIONS
1	V/A Rating		10A 250V AC
2	Contact resistance (Initial)		10 m ohms max.
3	Insulation resistance at 500 V DC		1000 M ohms min.
4	H.V.Break down test (For 1minute)		2 KV AC
5	Panel thickness maximum Other : Available on request *		Standard : 1.00 mm (A)
6	Mounting		Panel, Snap-In
7	Terminals		Solder-type / Fast-on
8	Permissible temp.	(a) With/Without load	0 To 65°C
		(b) For Soldering	270°C for 5 Sec. max.
9	Material	(a) Body, Flame retardant	Nylon-6, GF20%, V-2
		(b) Contacts, Terminals	Brass, Tin plating
10	Reference standards		IEC-60320-1
11	Approvals		CE RoHS

PRODUCT :
C13x2 Live Isolated

CODE :
EMO-12-A-1V2

APP 02.05.15 GJG
CHK 02.05.15 PGP
DRN 02.05.15 Vicky



ELCOM HOUSE
M.B.LOHIA MARG
413/1/1-A,
GANDHINAGAR
KOLHAPUR-416 119

Elcom International Pvt. Ltd.

REV	IS			WAS		DATE	SIGN	APP.	BY	DATE	SIGN	Elcom International Pvt. Ltd.													
UNSP.TOLERANCE				DIMNS. IN		WT(Gm)		SCALE:—		PROJECTION		SHEET		DRAWING NUMBER											
OVER	—	1	10	mm		Max.		NTS.				1 OF 1		P	E	M	O	2	0	1	2	REVISION			
UP TO	1	10	—	Moulding, plating details as per Bill of Material																				RO	
±	0.2	0.3	0.5	Unspecified colour is Black, GF:Glass filled.																					