


DATASHEET

A10

SPECIFICATIONS:



Industry Standard Dimensions



Chemical System: Zinc Air (Zn/O₂)

Identification: IEC-PR70

Tab Color: Yellow

Build Standard: IEC 60086-2:2000,
IEC 60086-2:2011

Nominal Voltage: 1.4 Volts

Capacity (IEC 60086-2:2000): 95 mAh (to 0.90 volts)
(Rated at 3000 ohms at 20°C/ 60%RH)

Capacity (IEC 60086-2:2011): 90 mAh (to 1.05 volts)
(Rated at 0.7 mA continuous & 3 mA / 100 ms Pulses at 25°C/ 60%RH)

Capacity Retention: > 85%(after 3 years)

Available Current: 4 mA(at 1.1 volts)

Tab Sealing Arrangements: On Cathode Can. See picture above.

Shelf Life: 3 years

Operation Temp: 0°C to 50°C


Typical Weight: 0.28 grams (0.01 oz.)

Typical Volume: 0.08 cubic centimeters
(0.005 cubic inch)


Impedance: ≤ 8 ohms (at AC 1000Hz)

IEC 60086-2:2000 Standards

DISCHARGE CHARACTERISTICS AT 3KΩ 25°C 60%RH
(Discharged 24 hours/day)



Construction





This data sheet is subject to change without prior notice.
Contact us for the latest information. Contents here do not
constitute a warranty. May 2011

DATASHEET

A10

Discharge Charts of IEC 60086-2:2011 Standards



This data sheet is subject to change without prior notice.
Contact us for the latest information. Contents here do not
constitute a warranty.
May 2011