

---

# PRODUCT SPECIFICATIONS

For Customer: \_\_\_\_\_  : APPROVAL FOR SPECIFICATION

Customer Model No. \_\_\_\_\_  : APPROVAL FOR SAMPLE

Module No.: **IE-SN-1316CH07R24-C0-1**

Date : 2019.03.14

Version :A

## 1. Table of Contents

| No. | Item   | Page |
|-----|--|------|
| 1   | Cover Sheet(Table of Contents)                       |      |
| 2   | Revision Record                                      |      |
| 3   | General Specifications                               |      |
| 4   | Outline Drawing                                      |      |
| 5   | Absolute Maximum Ratings                             |      |
| 6   | Electrical Specifications and Timing Characteristics |      |
| 7   | Optical Characteristics                              |      |
| 8   | Reliability Test Items and Criteria                  |      |
| 9   | Quality Level  |      |
| 10  | Packing Reliability                                  |      |

### For Customer's Acceptance:

| Approved By | Comment |
|-------------|---------|
|             |         |

| PREPARED | CHECKED | VERIFIED BY QA<br>DEPT | VERIFIED BY R&D<br>DEPT |
|----------|---------|------------------------|-------------------------|
|          |         |                        |                         |

---

## 2. Revision Record

| Date       | Rev.No. | Page | Revision Items    | Prepared |
|------------|---------|------|-------------------|----------|
| 2019.03.14 | A       |      | The first release |          |
|            |         |      |                   |          |

---

### 3. General Specifications

**IE-SN-1316CH07R24-C0-1** is a TFT-LCD module. It is composed of a TFT-LCD panel, driver IC, FPC, a back light unit. The 5.0" display area contains 800 x 480 pixels and can display up to 16.7M colors. This product accords with RoHS environmental criterion.

| Item                  | Contents                      | Unit    | Note |
|-----------------------|-------------------------------|---------|------|
| LCD Type              | TFT                           | -       |      |
| Display color         | 16.7M                         |         | 1    |
| Viewing Direction     | ALL                           | O'Clock |      |
| Operating temperature | -20~+70                       | °C      |      |
| Storage temperature   | -30~+80                       | °C      |      |
| Module size           | 120.70(W)×75.80(H)×3.0/4.2(T) | mm      | 2    |
| Active Area(W×H)      | 108×64.8                      | mm      |      |
| Number of Dots        | 800×RGB×480                   | dots    |      |
| Drive IC              | ST7262                        | -       |      |
| Power Supply Voltage  | 3.3                           | V       |      |
| Backlight             | 18-LEDs (white)               | pcs     |      |
| Data Transfer         | RGB 24-bit                    | -       |      |
| Weight                | ---                           | g       |      |

Note 1: Color tune is slightly changed by temperature and driving voltage.

Note 2: Without FPC and Solder.



## 5. Absolute Maximum Ratings(Ta=25°C)

### 5.1 Electrical Absolute Maximum Ratings.(Vss=0V ,Ta=25°C)

| Item                 | Symbol           | Min. | Max.    | Unit | Note |
|----------------------|------------------|------|---------|------|------|
| Power Supply Voltage | VDD              | -0.3 | 3.6     | V    | 1, 2 |
| Input Voltage        | V <sub>In</sub>  | -0.3 | VDD+0.5 | V    |      |
| Current of LED       | I <sub>LED</sub> | 0    | 60      | mA   |      |

Notes:

1. If the module is above these absolute maximum ratings. It may become permanently damaged.  
Using the module within the following electrical characteristic conditions are also exceeded, the module will malfunction and cause poor reliability.
2. VDD>V<sub>SS</sub> must be maintained.
3. Please be sure users are grounded when handling LCD Module.

### 5.2 Environmental Absolute Maximum Ratings.

| Item                | Storage |      | Operating |      | Note |
|---------------------|---------|------|-----------|------|------|
|                     | MIN.    | MAX. | MIN.      | MAX. |      |
| Ambient Temperature | -30°C   | 80°C | -20°C     | 70°C | 1,2  |
| Humidity            | -       | -    | -         | -    | 3    |

1. The response time will become lower when operated at low temperature.
2. Background color changes slightly depending on ambient temperature.

The phenomenon is reversible.

3. Ta<=40°C:85%RH MAX.

Ta>=40°C:Absolute humidity must be lower than the humidity of 85%RH at 40°C.

## 6. Electrical Specifications and Timing Characteristics

### 6.1 Electrical characteristics(V<sub>SS</sub>=0V ,T<sub>a</sub>=25°C)

| Parameter           | Symbol           | Condition            | Min      | Typ    | Max  | Unit   | Note |  |
|---------------------|------------------|----------------------|----------|--------|------|--------|------|--|
| Power supply        | VDD              | T <sub>a</sub> =25°C | 3.0      | 3.3    | 3.6  | V      |      |  |
| Input voltage       | 'H'              | V <sub>IH</sub>      | VDD=3.3V | 0.7VDD | -    | VDD    | V    |  |
|                     | 'L'              | V <sub>IL</sub>      | VDD=3.3V | 0      | -    | 0.3VDD | V    |  |
| Current Consumption | I <sub>CC1</sub> | Normal mode          | -        | -      | -    | mA     | 2    |  |
|                     | I <sub>CC2</sub> | Sleep mode           | -        | 0.03   | 0.09 | mA     | 2    |  |

Note:

1:When an optimum contrast is obtained in transmissive mode.

2: Tested in 1×1 chessboard pattern.

### 6.2 LED backlight specification(V<sub>SS</sub>=0V ,T<sub>a</sub>=25°C)

| Item            | Symbol         | Condition       | Min | Typ  | Max | Unit | Note |
|-----------------|----------------|-----------------|-----|------|-----|------|------|
| Supply voltage  | -              | -               | -   | 19.2 | -   | V    | 1    |
| Supply current  | I <sub>f</sub> | -               | -   | 60   | -   | mA   | 2    |
| Forward current | Normal         | I <sub>pn</sub> | -   | 60   | -   | mA   |      |
|                 | Dimming        | I <sub>pd</sub> | -   | -    | -   |      |      |


Note:

1: V<sub>LED</sub>=V<sub>LED</sub>(+)-V<sub>LED</sub>(-).

2:The current of LED is 20mA.

A LED drive in constant current mode is recommended.


3: LED power consumption is around 0.768W.




### 6.3 Interface signals


| Pin   | Symbol | Description.                  |
|-------|--------|-------------------------------|
| 1     | LED_K  | LED back light(Cathode)       |
| 2     | LED_A  | LED back light(Anode)         |
| 3     | GND    | GND                           |
| 4     | VDD    | Power supply                  |
| 5~12  | R0-R7  | Red data bus                  |
| 13~20 | G0-G7  | Green data bus                |
| 21~28 | B0-B7  | Blue data bus                 |
| 29    | GND    | GND                           |
| 30    | PCLK   | Data clock                    |
| 31    | DISP   | Standby mode select pin       |
| 32    | HSYNC  | Line SYNC signal              |
| 33    | VSYNC  | Frame SYNC signal             |
| 34    | DE     | Data Enable Input             |
| 35    | NC     | NC                            |
| 36    | GND    | GND                           |
| 37    | X1/NC  | Touch Panel Control Pin or NC |
| 38    | Y1/NC  | Touch Panel Control Pin or NC |
| 39    | X2/NC  | Touch Panel Control Pin or NC |
| 40    | Y2/NC  | Touch Panel Control Pin or NC |

## 6.4 Timing Characteristics





**SYNC-DE Mode**



### DE Mode

Parallel 24-bit RGB Input Timing (PVDD=PVDD1=VDD=VDDI= 3.3V, AGND= 0V, TA=25°C)

| Parallel 24-bit RGB Interface Timing Table |                |        |      |      |      |        |  |
|--|----------------|--------|------|------|------|--------|--|
| Item                                       | Symbol         | Min.   | Typ. | Max. | Unit | Remark |  |
| DCLK Frequency                             | Fclk           | 23     | 25   | 27   | MHz  |        |  |
| HSYNC                                      | Period Time    | Th     | 808  | 816  | 896  | DCLK   |  |
|  | Display Period | Thdisp | 800  |      |      | DCLK   |  |
|  | Back Porch     | Thbp   | 4    | 8    | 48   | DCLK   |  |
|  | Front Porch    | Thfp   | 4    | 8    | 48   | DCLK   |  |
|  | Pulse Width    | Thw    | 2    | 4    | 8    | DCLK   |  |
| VSYNC                                      | Period Time    | Tv     | 492  | 496  | 504  | HSYNC  |  |
|  | Display Period | Tvdisp | 480  |      |      | HSYNC  |  |
|  | Back Porch     | Tvbp   | 6    | 8    | 12   | HSYNC  |  |
|  | Front Porch    | Tvfp   | 6    | 8    | 12   | HSYNC  |  |
|  | Pulse Width    | Tvw    | 2    | 4    | 8    | HSYNC  |  |

Note: 1. The minimum blanking time depends on the GIP timing of the panel specification

2. To ensure the compatibility of different panels, it is recommended to use the typical setting.

3. It is necessary to keep Tvbp =12 and Thbp =43 in sync mode. DE mode is unnecessary to keep it.

## 7. Optical Characteristics

| Item                    | Symbol      | Condition        | Min. | Typ. | Max. | Unit              | Note |
|-------------------------|-------------|------------------|------|------|------|-------------------|------|
| Brightness              | Bp          | $\theta=0^\circ$ | 500  | 520  | 550  | Cd/m <sup>2</sup> | 1    |
| Uniformity              | $\Delta Bp$ | $\Phi=0^\circ$   | 70   | 80   | -    | %                 | 1,2  |
| Viewing Angle           | 3:00        | $Cr \geq 10$     | -    | 80   | -    | Deg               | 3    |
|                         | 6:00        |                  | -    | 80   | -    |                   |      |
|                         | 9:00        |                  | -    | 80   | -    |                   |      |
|                         | 12:00       |                  | -    | 80   | -    |                   |      |
| Contrast Ratio          | Cr          | $\theta=0^\circ$ | -    | 1500 | -    | -                 | 4    |
| Response Time           | $T_r+T_f$   | $\Phi=0^\circ$   | -    | 30   | -    | ms                | 5    |
| Color of CIE Coordinate | W           | x                | 0.26 | 0.31 | 0.36 | -                 | 1,6  |
|                         |             | y                | 0.28 | 0.33 | 0.38 | -                 |      |
|                         |             | Y                | -    | -    | -    | -                 |      |
|                         | R           | x                | -    | -    | -    | -                 |      |
|                         |             | y                | -    | -    | -    | -                 |      |
|                         |             | Y                | -    | -    | -    | -                 |      |
|                         | G           | x                | -    | -    | -    | -                 |      |
|                         |             | y                | -    | -    | -    | -                 |      |
|                         |             | Y                | -    | -    | -    | -                 |      |
|                         | B           | x                | -    | -    | -    | -                 |      |
|                         |             | y                | -    | -    | -    | -                 |      |
|                         |             | Y                | -    | -    | -    | -                 |      |
| NTSC Ratio              | S           | $\theta=0^\circ$ | -    | 60   | -    | %                 |      |


Note: The parameter is slightly changed by temperature, driving voltage and material

Note 1: The data are measured after LEDs are turned on for 5 minutes. LCM displays full white. The brightness is the average value of 9 measured spots. Measurement equipment PR-705 ( $\Phi 8\text{mm}$ )

Measuring condition:

- Measuring surroundings: Dark room.
- Measuring temperature:  $T_a=25^\circ\text{C}$ .
- Adjust operating voltage to get optimum contrast at the center of the display.

Measured value at the center point of LCD panel after more than 5 minutes while backlight turning on.




Note 2: The luminance uniformity is calculated by using following formula.

$$\Delta B_p = B_p (\text{Min.}) / B_p (\text{Max.}) \times 100 (\%)$$


$B_p (\text{Max.})$  = Maximum brightness in 9 measured spots

$B_p (\text{Min.})$  = Minimum brightness in 9 measured spots.




Note 3: The definition of viewing angle:

Refer to the graph below marked by  $\theta$  and  $\phi$




Note 4: Definition of contrast ratio.( Test LCD using DMS501)



$$\text{Contrast ratio}(Cr) = \frac{\text{Brightness of selected dots}}{\text{Brightness of non-selected dots}}$$


Note 5: Definition of Response time. (Test LCD using DMS501):

The output signals of photo detector are measured when the input signals are changed from “black” to “white”(falling time) and from “white” to “black”(rising time), respectively. The response time is defined as the time interval between the 10% and 90% of amplitudes.Refer to figure as below.



The definition of response time

Note 6: Definition of Color of CIE Coordinate and NTSC Ratio.




Color gamut:

$$S = \frac{\text{area of RGB triangle}}{\text{area of NTSC triangle}} \times 100\%$$

Note 7: Definition of cross talk.

Cross talk ratio(%) = | pattern A Brightness - pattern B Brightness | / pattern A Brightness \* 100



Electric volume value =  $3F \pm 3Hex$

## 8. Reliability Test Items and Criteria

| No | Test Item                           | Test condition  | Criterion  |
|----|-------------------------------------|---|--|
| 1  | High Temperature Storage            | 80°C±2°C 96H<br>Restore 2H at 25°C<br>Power off   | 1. After testing, cosmetic and electrical defects should not happen.<br>2. Total current consumption should not be more than twice of initial value. |
| 2  | Low Temperature Storage             | -30°C±2°C 96H<br>Restore 2H at 25°C<br>Power off  |  |
| 3  | High Temperature Operation          | 70°C±2°C 96H<br>Restore 2H at 25°C<br>Power on  |  |
| 4  | Low Temperature Operation           | -20°C±2°C 96H<br>Restore 4H at 25°C<br>Power on   |  |
| 5  | High Temperature/Humidity Operation | 50°C±2°C 90%RH 96H<br>Power on  |  |
| 6  | Temperature Cycle(Storage)          | -20°C ← -25°C -----> 70°C<br>30min 5min 30min<br>after 5 cycle, Restore 2H at 25°C<br>Power off |  |
| 7  | Vibration Test                      | 10Hz~150Hz, 100m/s <sup>2</sup> , 120min  | Not allowed cosmetic and electrical defects.   |
| 8  | Shock Test                          | Half- sine wave, 300m/s <sup>2</sup> , 11ms   |  |
| 9  | ESD Test                            | Air discharge: +/-8KV,<br>Contact discharge: 4KV  |  |

Note: Operation: Supply 3.3V for logic system.

The inspection terms after reliability test, as below

| ITEM       | Inspection        |
|------------|-------------------|
| Contrast   | CR>50%            |
| IDD        | IDD<200%          |
| Brightness | Brightness>60%    |
| Color Tone | Color Tone+/-0,05 |

## 9 Quality level



### 9.1 Classification of defects

Major defects (MA): A major defect refers to a defect that may substantially

degrade usability for product applications, including all functional defects(such as no display, abnormal display, open or missing segment, short circuit, missing component), outline dimension beyond the drawing, progressive defects and those affecting reliability.

Minor defects (MI): A minor defect refers to a defect which is not considered to be able to substantially degrade the product application or a defect that deviates from existing standards almost unrelated to the effective use of the product or its operation, such as black spot, white spot, bright spot, pinhole, black line, white line, contrast variation, glass defect, polarizer defect, etc.

### 9.2 Definition of inspection range

|   |  |
|---|--|
| <p>For dot defect of TFT LCD which is not smaller than 3 inches, dividing three areas to make a judgment (according to figure 1).</p> <p>A area : center of viewing area<br/>         B area : periphery of viewing area<br/>         C area : Outside viewing area</p> <p>For other defects, dividing two areas to make a judgment (according to figure 2).</p> <p>A zone : Inside Viewing area<br/>         B zone : Outside Viewing area</p> <p>X1(A.A~V.A): 2mm    X2(A.A~V.A): 2mm<br/>         Y1(A.A~V.A): 2mm    Y2(A.A~V.A): 2mm</p> |  <p>Figure 1</p>  <p>Figure 2</p> |
|---|--|

### 9.3 Inspection items and general notes

|                  |   |   |
|------------------|---|---|
| General notes    | <p>1.Should any defects which are not specified in this standard happen, additional standard shall be determined by mutual agreement between customer and TIANMA.</p> <p>2.Viewing area should be the area which TIANMA guarantees.</p> <p>3.Limit sample should be prior to this Inspection standard.</p> <p>4.Viewing judgment should be under static pattern.</p> <p>5.Inspection conditions</p> <p style="padding-left: 20px;">Inspection distance: 250 mm (from the sample)      Temperature      : 25±5 °C</p> <p style="padding-left: 20px;">Inspection angle    : 45 degrees in 6 o'clock direction (all defects in viewing area should be inspected from this direction)</p> |   |
| Inspection items | Pinhole, Bright spot, Black spot, White spot, Black line, White Line, Foreign particle, Bubble  | The color of a small area is different from the remainder. The phenomenon doesn't change with voltage |
|                  | Contrast variation  | The color of a small area is different from the remainder. The phenomenon changes with voltage        |
|                  | Polarizer defect  | Scratch, Dirt, Particle, Bubble on polarizer or between polarizer and glass                           |
|                  | Dot defect (TFT LCD)  | The pixel appears bright or dark abnormally when display  |
|                  | Functional defect   | No display, Abnormal display, Open or missing segment, Short circuit, False viewing direction         |



|  |              |  |
|--|--------------|--|
|  | Glass defect | Glass crack, Shaved corner of glass, Surplus glass |
|  | PCB defect   | Components assembly defect                         |




#### 9.4 Outgoing Inspection level





| Outgoing Inspection standard | Inspection conditions | Inspection |      |      |    |       |
|------------------------------|-----------------------|------------|------|------|----|-------|
|                              |                       | Min.       | Max. | Unit | IL | AQL   |
| Major Defects                | See 8.3 general notes | See 8.5    |      |      | II | 0.065 |
| Minor Defects                | See 8.3 general notes | See 8.5    |      |      | II | 0.065 |

Note: Sampling standard conforms to GB2828

#### 9.5 Inspection Items and Criteria

| Inspection items           |   |                            | Judgment standard   |           |                   |           |
|----------------------------|---|----------------------------|---|-----------|-------------------|-----------|
|                            |   |                            | Category  |           | Acceptable number |           |
|                            |   |                            |   |           | A zone            | B zone    |
| 1                          |  <p><math>\Phi=(a+b)/2(\text{mm})</math><br/>(<math>a/b&lt;2.5</math>)</p> | A                          | $\Phi\leq 0.20$   | Neglected | Neglected         |           |
|                            |   | B                          | $0.20<\Phi\leq 0.25$  | 3         | Neglected         |           |
|                            |   | C                          | $0.25<\Phi\leq 0.3$   | 2         | Neglected         |           |
|                            |   | D                          | $0.3<\Phi\leq 0.4$  | 1         | 3                 |           |
|                            |   | E                          | $0.4<\Phi\leq 0.5$  | 0         | 2                 |           |
|                            |   | Total defective point(B,C) |   | 1         | -                 |           |
|                            |   | 2                          |  <p><math>L/W\geq 2.5</math></p> | A         | $W\leq 0.03$      | Neglected |
| B                          | $0.03<W\leq 0.05$<br>$L\leq 3.0$  |                            |   | 3         | Neglected         |           |
| C                          | $0.05<W\leq 0.1$<br>$L\leq 3.0$   |                            |   | 2         | Neglected         |           |
| D                          | $0.05<W\leq 0.1$<br>$L\leq 4.0$   |                            |   | 1         | 3                 |           |
| E                          | $W>0.1$<br>$L>4.0$  |                            |   | 0         | 2                 |           |
| Total defective point(B,C) |   |                            |   | 1         | -                 |           |

|    |   |   |   |                       |           |           |
|----|---|---|---|-----------------------|-----------|-----------|
| 3  | Bright spot                             |   | any size  | none                  | none      |           |
| 4  | Contrast variation                      |    | A   | $\Phi < 0.2$          | Neglected | Neglected |
|    |   |   | B   | $0.2 < \Phi \leq 0.3$ | 2         |           |
|    |   |   | C   | $0.3 < \Phi \leq 0.4$ | 1         |           |
|    |   |   | D   | $0.4 < \Phi$          | 0         |           |
|    |   |   | Total defective point(B,C)  |                       |           | 3         |
| 5  | Bubble inside cell                      |   | any size  | none                  | none      |           |
| 6  | Polarizer defect (if Polarizer is used) | Scratch ,damage on polarizer, Particle on polarizer or between polarizer and glass. | Refer to item 1 and item 2.   |                       |           |           |
|    |   | Bubble, dent and convex   | A   | $\Phi \leq 0.1$       | Neglected | Neglected |
|    |   |   | B   | $0.1 < \Phi \leq 0.2$ | 2         | Neglected |
|    |   |   | C   | $0.2 < \Phi \leq 0.3$ | 1         | 2         |
| 7  | Surplus glass                           | Stage surplus glass   | <br>$B \leq 0.3\text{mm}$                                  |                       |           |           |
|    |   | Surrounding surplus glass   | <br>Should not influence outline dimension and assembling. |                       |           |           |
| 8  | Open segment or open common             |   | Not permitted   |                       |           |           |
| 9  | Short circuit                           |   | Not permitted   |                       |           |           |
| 10 | False viewing direction                 |   | Not permitted   |                       |           |           |
| 11 | Contrast ratio uneven                   |   | According to the limit specimen   |                       |           |           |
| 12 | Crosstalk                               |   | According to the limit specimen   |                       |           |           |
| 13 | Black /White spot(display)              |   | Refer to item 1   |                       |           |           |
| 14 | Black /White line(display)              |   | Refer to item 2   |                       |           |           |

| Inspection items |  | Judgment standard   |  | Acceptable number   |                       |
|------------------|--|---|--|---|-----------------------|
|                  |  | Category(application: B zone)   |  |   |                       |
| 15               | Glass defect crack   | i )The front of lead terminals<br>   | A  | $a \leq t, b \leq 1/5W, c \leq 3\text{mm}$  | Max.3 defects allowed |
|                  |  |   | B  | Crack at two sides of lead terminals should not cover patterns and alignment mark |                       |
|                  |  | ii )Surrounding seal crack-non-contact side<br><br><u>Inner border line of the seal</u><br><u>Outer border line of the seal</u> |  | $b < \text{Inner borderline of the seal}$   |                       |
|                  |  | iii ) Surrounding seal crack- contact side<br><br><u>Inner border line of the seal</u><br><u>Outer border line of the seal</u> |  | $b < \text{Outer borderline of the seal}$   |                       |
|                  | iv)Corner<br> | A   | $a \leq t, b \leq 3.0, c \leq 3.0$                                       |   |                       |
|                  |  | B   | Glass crack should not cover patterns u and alignment mark and patterns. |   |                       |

| Inspection items |  | Judgment standard   |  |
|------------------|--|---|--|
|                  |  | Category(application: B zone)   |  |
| 16               | PCB defect   | <p>Component soldering:<br/>           No cold soldering、short、open circuit、burr、tin ball<br/>           The flat encapsulation component position deviation must be less than 1/3 width of the pin (Pic.1);<br/>           the sheet component deviation:<br/>           Pin deviates from the pad and contact with the near components is not permitted (Pic.2)</p> |  |
|                  |  | <p>lead defect:<br/>           The lead lack must be less than 1/3 of its width;<br/>           The lead burr must be less than 1/3 of the seam;<br/>           Impurities connect with the near leads is not permitted</p>   |  |
|                  |  | <p>Connector soldering:<br/>           Soldering tin is at contact position of the plug and socket is not permitted<br/>           No foundation is scald<br/>           Serious cave distortion on plug and socket contact pin is not permitted</p>  |  |
|                  | <p>Glue on root of the speaker receiver and motor lead:<br/>           The insulative coat of the lead must join into the PCB; the protected glue must envelop to the insulative coat.</p> |   |  |

---

## 10. Precautions for Use of LCD Modules

### 10.1 Handling Precautions

10.1.1 The display panel is made of glass. Do not subject it to a mechanical shock by dropping it from a high place, etc.

10.1.2 If the display panel is damaged and the liquid crystal substance inside it leaks out, be sure not to get any in your mouth, if the substance comes into contact with your skin or clothes, promptly wash it off using soap and water.

10.1.3 Do not apply excessive force to the display surface or the adjoining areas since this may cause the color tone to vary.

10.1.4 The polarizer covering the display surface of the LCD module is soft and easily scratched. Handle this polarizer carefully.

10.1.5 If the display surface is contaminated, breathe on the surface and gently wipe it with a soft dry cloth. If still not completely clear, moisten cloth with one of the following solvents:

- Isopropyl alcohol
- Ethyl alcohol

Solvents other than those mentioned above may damage the polarizer.

Especially, do not use the following:

- Water
- Ketone
- Aromatic solvents

10.1.6 Do not attempt to disassemble the LCD Module.

10.1.7 If the logic circuit power is off, do not apply the input signals.

10.1.8 To prevent destruction of the elements by static electricity, be careful to maintain an optimum work environment.

- a. Be sure to ground the body when handling the LCD Modules.
- b. Tools required for assembly, such as soldering irons, must be properly ground.
- c. To reduce the amount of static electricity generated, do not conduct

---

assembly and other work under dry conditions.

- d. The LCD Module is coated with a film to protect the display surface. Be care when peeling off this protective film since static electricity may be generated.

## **10.2 Storage precautions**

10.2.1 When storing the LCD modules, avoid exposure to direct sunlight or to the light of fluorescent lamps.

10.2.2 The LCD modules should be stored under the storage temperature range.

If the LCD modules will be stored for a long time, the recommend condition is:

Temperature :        0°C ~ 40°C

Relatively humidity: ≤80%

10.2.3 The LCD modules should be stored in the room without acid, alkali and harmful gas.

**10.3 The LCD modules should be no falling and violent shocking during transportation, and also should avoid excessive press, water, damp and sunshine.**