5.0mm Round Type LED Lamps

.....

MODEL NO: <u>IE-5Y4SD-3FT</u>

★Features:

- Low power consumption;
- High efficiency and high performance;
- Choice of various viewing angles;
- Reliable and robust.

★Lens Color:

☑ Color Diffused ☐ Color Transparent

□ Water Clear □ White Diffused


★Descriptions:

- The series is specially designed for applications requiring higher brightness.
- The led lamps are available with different Colors, intensities, epoxy colors, etc.

★Applications:

- Indicators
- Home electric appliance
- Automotive
- Sign & Signal.

★Package Dimension:



*Attention

- 1, All dimensions are in millimeters (inches).
- 2. Tolerance is ± 0.25 mm(0.01") unless otherwise specified.
- 3. The outstanding gum edge part is biggest not very in 1.5mms.
- 4. The long feet is a LED Anode.

★Absolute Maximum Ratings(Ta=25°C):

_						
Parameter	Symbol	Rating	Unit	Remark		
Forward Current	I_{F}	30	m A			
Peak Forward Current	$I_{ t FP}$	100	100 m A 1/10			
Reverse Voltage	V_{R}	5	V			
Operating Temperature	Topr	-25 ~+85	℃			
Storage Temperature	TStg	-40 ~+100	℃			
Soldering Temperature	Tsol	260	$^{\circ}\mathbb{C}$	≤3 seconds		
Power Dissipation	Pd	60	mW			

\bigstar Electronic Optical Characteristics (Ta=25°C):

Part Number	Emitting - Color	$V_F(V)$ $I_F=20 \mathrm{mA}$		I V(mcd) I _F =20mA		$I_{R}(\mu A)$	$\lambda_{ \text{m}} (\text{nm})$	Δλ(nm)	1 1111810 1	
		Min	Тур	Max	Тур	Max	VR=5V			2θ _{1/2} (°)
IE-5Y4SD-3FT	YELLOW	1.8	2.0	2.4	180	520	<10	586-594	20	40°

★Elucidation: Pb = Pb free Soldering Application, Pb < 1000ppm (RoHS-Compliant)