10mm Round Type LED Lamps

MODEL NO: IE-10WW-SB-D-C

★Features:

- Fluorescence Type;
- High Luminous Intensity;
- High Efficienty;

★Lens Color:

- □ Color Diffused □ Color Transparent
- □ Water Clear ☑ White Diffused


★Descriptions:

• The white LED which was fabricated using a blue LED and a phosphor, and the phosphor is excited by blue light and emits yellow fluorescence. The mixture of blue light and yellow light results in a white emission.

*Applications:

- OA Equipment;
- Backlighting of LCD;
- Automotive Equipment;
- Replacement of Conventional Light Bulbs and Fluorescent Lamps.

★Package Dimension:



*Attention

- 1, All dimensions are in millimeters (inches).
- 2, Tolerance is ± 0.25 mm(0.01") unless otherwise specified.
- 3. The outstanding gum edge part is biggest not very in 1.5mms.
- 4. The long feet is a LED Anode.

\bigstar Absolute Maximum Ratings (Ta=25°C):

Parameter	Symbol	Rating	Unit	Remarks	
Forward Current	I_{F}	30	m A		
Peak Forward Current	I_{FP}	100	m A	1/10 Duty Cycle	
Reverse Voltage	V_{R}	5	V		
Operating Temperature	Topr	-25~+85	$^{\circ}\!\mathbb{C}$		
Storage Temperature	Tstg	-40 ~+100	$^{\circ}$		
Soldering Temperature	Tsol	260 ℃		≪3 seconds	
Power Dissipation	Pd	80	mW		

\bigstar Electronic Optical Characteristics (Ta=25°C):

Part Number	Emitting Color	$V_{F}(V)$ $I_{F}=20$ mA		$I_{\rm F}$ V(mcd) $I_{\rm F}$ = 20mA		$I_R(\mu A)$	Chromaticity Coordinates		Viewing Angle	
		Min	Тур	Max	Тур	Max	VR=5V	X	Y	2θ _{1/2} (°)
IE-10WW-SB- D-C	Warm White	2.8	3.0	3.6	1150	2800	< 10	0.46-0.50	0.44-0.47	130°

★Elucidation: Pb = Pb free Soldering Application, Pb < 1000ppm (RoHS-Compliant)

▲ TEL: 0750-3862666 3862686

▲ FAX: 0750-3862678

▲ Infrared LEDs ▲ LCD Backlight

▲ WEB: http://www.jmcl.cn

▲ E-mail: changliled@21cn.com ▲ ADD: NO. 36 Bangmin Road Jianghai Distict Jiangmen China

▲ LEDs ▲ LED Displays

▲ LED Light