


# SPECIFICATION FOR APPROVAL

<b>Customer Name</b>	
<b>Product Name</b>	Through Hole-LED
<b>Model No.</b>	IE-P05THBR620
<b>Description</b>	5mm Bullet Red LED
<b>Date</b>	2007/9/1
<b>Sample No.</b>	

<b>Clients (Signature) :</b> DD    MM    YYYY
---

# SPECIFICATION FOR APPROVAL


## Package Dimensions



### Notes

1. All dimensions are in millimeters (inches).
2. Tolerance is  $\pm 0.25\text{mm}$  ( $0.010''$ ) unless otherwise noted.
3. Protruded resin under flange is  $1.0\text{mm}$  ( $0.04''$ ) max.
4. Lead spacing is measured where the leads emerge from the package.
5. Specifications are subject to change without notice.

## Spatial Distribution



PART NUMBER	REV	PAGE	DATE
IE-P05THBR620	R101	1/3	2007-09-01

## SPECIFICATION FOR APPROVAL

### Electrical / Optical Characteristics at TA=25°C

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Luminous Intensity	LM	12000		14000	mcd	IF = 30mA
Viewing Angle	2 θ 1/2	10		15	deg	IF = 30mA
Dominant Wavelength	Tc	620		630	nm	IF = 30mA
Spectral Line Half-Width	Δ λ				nm	IF = 30mA
Forward Voltage	VF	2.0	2.2	2.4	V	IF = 30mA
Reverse Current	IR			20	μ A	VR = 5V






### Absolute Maximum Ratings at TA=25°C

Parameter	Maximum Rating
Power Dissipation	0.06W
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	60mA
Continuous Forward Current	30mA
Derating Linear From 30°C	0.5mA/°C
Reverse Voltage	5V
Operating Temperature Range	-20°C to + 80°C
Storage Temperature Range	-30°C to + 100°C
Lead Soldering Temperature [1.6mm(.063") From Body]	260°C for 5 Seconds

PART NUMBER	REV	PAGE	DATE
IE-P05THBR620	R101	2/3	2007-09-01

# SPECIFICATION FOR APPROVAL

## Typical Electro-Optical Characteristics Curves



- ① Blue Lamp(InGaN)
- ② White Lamp(InGaN)
- ③ Pure Green Lamp(InGaN)
- ④ Yellow Green Lamp(AlInGaP)
- ⑤ Red Lamp(AlInGaP)
- ⑥ Infrared Lamp(850nm)

PART NUMBER	REV	PAGE	DATE
IE-P05THBR620	R101	3/3	2007-09-01